

INDUSTRIAL TYPE – **WATER HEATED** AIR CURTAINS
133 mm cross flow fan



KWH - 26



For use in :

- Large Industrial Spaces**
- Storage Plants**
- Storage Areas**
- Airports**
- Cold Rooms**



INDUSTRIAL TYPE – WATER HEATED AIR CURTAINS

133 mm cross flow fan




Air Curtain KWH– 26 is capable of covering openings of 1.60 m long

Technical Details


		Water Inlet – Outlet Temperature 60 °C – 50 °C	Water Inlet – Outlet Temperature 80 °C – 65 °C
Max Door Height (m)		5.5	
Max Door Width (m)		1.2	
Air Inlet Temperature		20 °C	
Heating Power (kW)	HI	8.0	14.0
	LOW	7.0	12.0
Air Outlet Temperature	HI	32 °C	37 °C
	LOW	31 °C	34 °C
Pressure Drop Water (ΔP) (Pa)	HI	420	480
	LOW	330	350
Flow Rate (lt/sec)	HI	0.20	0.20
	LOW	0.20	0.20
Outlet Velocity (m/sec)	HI	11.0	
	LOW	8.5	
Air Volume (m³/h)	HI	2390	
	LOW	1845	
Noise level in 1 m dB(A)	HI	67	
	LOW	64	
Motor Power (W)		660	
Capacitor (μF)		12	
Power Supply		230 V , 1 N , 50 Hz	
Capacity (lt)		0.8	
Weight with water (kg)		33	
Weight without water (kg)		32	

AIR VELOCITY
DISTRIBUTION
CHART



Dimensions

A: Total Length	1255±2 (mm)
B: Total Width	306 (mm)
C: Height	227 (mm)
D: Outlet Length	1200 (mm)
E: Outlet Width (int.)	60 (mm)
K: Outlet width (ext.)	76 (mm)
H: Outlet Height	64 (mm)



INDUSTRIAL TYPE – WATER HEATED AIR CURTAINS
133 mm cross flow fan



OPERATIONAL CHOICES

A) Wired Remote Control Operation

Wall Mounted Wired Remote Control
(from 2.5m up to 6 m cable)
which additionally can be supplied
with an Infrared Remote Control as well.



B) Infrared Remote Control Operation

Unit is provided with a build in Panel
(electronic) and an infrared Remote Control.



**Both above described options
can be either delivered :**

- 1). Two speed operation (HI - LOW)
- 2). NL operation :
 - 15 different speeds
 - 1 up to 240 units in parallel connection
 - Master - Slave Operation
 - OLEFINI BMS monitoring

